



**1A66-641**

## LINE VOLTAGE WALL THERMOSTATS

Electric Heat Thermostats used for Controlling Baseboards, Cable Heat, Glass Panels, etc.

### FEATURES

- 1A66 types are a double-pole disconnect model with "OFF" position which mechanically breaks both sides of line.
- Classic White or Beige color.

### SPECIFICATIONS

Dimensions . . . . . 4<sup>1</sup>/<sub>2</sub>" H x 2<sup>3</sup>/<sub>4</sub>" W x 1<sup>1</sup>/<sub>4</sub>" D  
Agency . . . . . U.L. listed and C.S.A. certified

### PARTS AND ACCESSORIES

 See end of this section for additional parts and accessories

- F61-2152 – Wallplate (6<sup>5</sup>/<sub>8</sub>" x 4<sup>5</sup>/<sub>8</sub>" )
- F75-0176 – for locking or limiting temperatures at 66°, 69°, 72° or 75°F  
Temperature limit can also be set at 60° or 63°F
- Thermostat guards – see pages 26-27

Model Number	Range	Differential	Switch Action	Resistive (Non-Inductive)
1A65-641	40 to 85°F (4 to 29°C)	1.0°F	Open on Rise	22.0A, 120 VAC (2500W)
1A65W-641 ①				22.0A, 240 VAC (5000W) 18.0A, 277 VAC (5000W)
1A66-641	40 to 85°F (4 to 29°C)	1.0°F	Open on Rise	22.0A, 240 VAC (5000W)
1A66W-641 ①				18.0A, 277 VAC (5000W)
1A65-610 ②	40 to 85°F (4 to 29°C)	1.0°F	Open on Rise	22.0A, 120 VAC (2500W)
1A65-633				22.0A, 240 VAC (5000W)
1A65W-633 ①				18.0A, 277 VAC (5000W)
1A66-633	40 to 85°F (4 to 29°C)	1.0°F	Open on Rise	22.0A, 240 VAC (5000W)
1A66W-633 ①				18.0A, 277 VAC (5000W)

① W in model number denotes Classic White Color

② Model 1A65-610 features tamperproof setting

REPLACES HONEYWELL T498A/B SERIES



**1G66-641**

## LINE VOLTAGE BIMETAL WALL THERMOSTATS

Electric Heat Thermostats used for Controlling Baseboards, Cable Heat, Glass Panels, etc.

### FEATURES

- 1G66 types are a double-pole disconnect model with "OFF" position which mechanically breaks both sides of line.
- Classic white.

### SPECIFICATIONS

Dimensions . . . . . 4<sup>13</sup>/<sub>16</sub>" H x 3<sup>5</sup>/<sub>16</sub>" W x 1<sup>7</sup>/<sub>16</sub>" D  
Agency . . . . . U.L. listed and C.S.A. certified

### PARTS AND ACCESSORIES

 See end of this section for additional parts and accessories

- F61-2685 – Wallplate (4<sup>3</sup>/<sub>16</sub>" x 5<sup>11</sup>/<sub>16</sub>" )
- Thermostat guards – see pages 26-27

	Model Number	Range	Differential	Switch Action	Resistive (Non-Inductive)
NEW!	1G65-641	40 to 80°F (4 to 26°C)	2.0°F	Open on Rise	22.0A, 120 VAC (2500W) 22.0A, 240 VAC (5000W) 18.0A, 277 VAC (5000W)
NEW!	1G66-641	40 to 80°F (4 to 26°C)	2.0°F	Open on Rise	22.0A, 240 VAC (5000W) 18.0A, 277 VAC (5000W)
NEW! *	1G65-633	40 to 80°F (4 to 26°C)	1.0°F	Open on Rise	22.0A, 120 VAC (2500W) 22.0A, 240 VAC (5000W) 18.0A, 277 VAC (5000W)
NEW! *	1G66-633	40 to 80°F (4 to 26°C)	1.0°F	Open on Rise	22.0A, 240 VAC (5000W) 18.0A, 277 VAC (5000W)

\* Indicates Canadian Model Number: call 1-905-201-4653 to order