

American ALDES' Model EFLTC Electronic Fan-Light Timer Switch Control is ideal for controlling a 120 V load, such as a fan, ZRT or light. Use for turning "ON" fan and light circuits simultaneously and turning light manually "OFF" allowing fan to remain on for a manually pre-set delay time of 20, 40 or 60 minutes.

The LED display can be easily viewed in darkened rooms and indicates ON-OFF status and pre-set time delays of 20, 40, or 60 minutes. The selected delay time remains in memory until it is changed by the user.

The Decora™ styled EFLTC fits single or multi-gang wall boxes, and includes both white and ivory overlays. Used in Residential and Commercial Bathrooms. 120VAC, 60Hz, 1/6 HP, 500W Incandescent.



OPERATION INSTRUCTIONS

- The "SWITCH LOCATOR" LED is intended to remain ON to assist finding the switch in a darkened room.
- Press the top "ON/OFF" switch once to turn the fan and light ON.
- Press the top "ON/OFF" switch again to turn the light OFF. NOTE: the fan will remain ON for the selected time delay (factory default setting is 20 minutes).
- When the time delay is completed, the fan will automatically shut OFF.
- Press the bottom "TIME DELAY SELECTION SWITCH" to cycle the fan time delay to 20, 40, or 60 minutes. The corresponding LEDs will light indicating the selected time period.

NOTE: Both "TIME DELAY" LEDs indicate a 60 minute time period.

INSTALLATION INSTRUCTIONS

- 1) TURN POWER OFF at circuit breaker or fuse panel.
- 2) Remove wall plate and existing switch from the wall box if one is presently installed.
- 3) Select white or ivory overlay matching decorator style wall plate to be used. Peel protective backing, and apply overlay to front, rectangular recess of time switch. Be sure to align pushbutton and LED locations of overlay to time switch.
- 4) Referring to Wiring Diagram, connect the wires from the fan/light time switch to the wires in the wall box using the wire nuts provided.
- 5) Carefully place wires and switch into wall box, and secure with two mounting screws provided.
- 6) Install decorator style wall plate (not included).
- 7) Turn power ON at circuit breaker or fuse panel.

