

4396510 - Refrigerator Filter

Replacement cartridge NLC240V for Filter Model WF-NLC240V
Replacement cartridge LC400V for Filter Model WF-LC400V

Operating Parameters:

Temperature: Min. 33°F (0.6°C) Max. 100°F (38°C)
Working Pressure: Min. 30 psi (207 kPa)
Max. 120 psi (827 kPa)
Flow Rate: 0.5 gpm (1.89 Lpm)
Capacity: 400 gallons with indicator
(1,514 liters) – WF-LC400V
240 gallons without indicator
(908 liters) – WF-NLC240V

This is a mechanical and chemical reduction filter.

NSF International, a nationally recognized not-for-profit agency for the certification of water filters, has tested and certified this product to reduce the following list of contaminants. Products with the NSF mark are certified to pass a series of stringent independent tests.

Tested and certified by NSF International in models WF-NLC240V and WF-LC400V against NSF/ANSI Standard 42 for the reduction of Chlorine Taste and Odor and Nominal Particulate Reduction Class I and against NSF/ANSI Standard 53 for the reduction of Lead, Mercury, Benzene, p-Dichlorobenzene, Toxaphene, 2, 4-D, Asbestos, Cysts, Turbidity and Atrazine.



The contaminants or other substances removed or reduced by this water filter are not necessarily in all users' water.

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems that are certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

IMPORTANT NOTICE - Read the manufacturer's Product Data Sheet. California Department of Public Health Certification # 03-1551. For conditions of use, health claims certified by the California Department of Public Health and replacement parts, see product data sheet.