

4396701 - Refrigerator Filter

Replacement cartridge NL120V for Filter Model WF-NL120V

Replacement cartridge L200V for Filter Model WF-L200V

Operating Parameters:

Temperature: Min. 33°F (0.6°C) Max. 100°F (38°C)

Working Pressure: Min. 30 psi (207 kPa)
Max. 120 psi (827 kPa)

Flow Rate: 0.5 gpm (1.89 Lpm)

Capacity: 200 gallons with indicator (757 liters)

– WF-L200V

120 gallons without indicator

(454 liters) – WF-NL120V

This is a mechanical and chemical reduction filter.

NSF International, a nationally recognized not-for-profit agency for the certification of water filters, has tested and certified this product to reduce the following list of contaminants. Products with the NSF mark are certified to pass a series of stringent independent tests.

Tested and certified by NSF International in models WF-L200V and WF-NL120V against NSF/ANSI Standard 42 for the reduction of Chlorine Taste and Odor and Nominal Particulate Reduction Class III and against NSF/ANSI Standard 53 for the reduction of Lead, Mercury, Benzene, p-Dichlorobenzene, Toxaphene, Ethylbenzene, O-Dichlorobenzene, and 1,2,4-Trichlorobenzene.



The contaminants or other substances removed or reduced by this water filter are not necessarily in all users' water.

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

IMPORTANT NOTICE - Read the manufacturer's Product Data Sheet. California Department of Public Health Certification # 04-1612. For conditions of use, health claims certified by the California Department of Public Health, and replacement parts, see product data sheet.