

4396710 - Refrigerator Filter

Replacement cartridge # P1RFBW2 for Model # P1WB2L, and P1WB2

Operating Parameters:

Temperature:	Min. 33°F (0.6°C) Max. 100°F (38°C)
Working Pressure:	Min. 30 psi (207 kPa) Max. 120 psi (827 kPa)
Flow Rate:	0.5 gpm (1.89 Lpm)
Capacity:	200 gallons (757 liters)

This is a mechanical and chemical reduction filter.

NSF International, a nationally recognized not-for-profit agency for the certification of water filters, has tested and certified this product to reduce the following list of contaminants. Products with the NSF mark are certified to pass a series of stringent independent tests.



REPLACEMENT
ELEMENT

Tested and certified by NSF International against NSF/ANSI Standard 53 in model numbers P1WB2L and P1WB2 for the reduction of Lead, Cysts, Turbidity, Asbestos, Mercury, Toxaphene, Atrazine, Lindane, Alachlor, Endrin, Benzene, o-Dichlorobenzene, Tetrachloroethylene, Ethylbenzene, Chlorobenzene and Styrene and Standard 42 for Chlorine Taste and Odor, and Nominal Particulate Reduction Class I.

The contaminants or other substances removed or reduced by this water filter are not necessarily in all users' water.

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems that are certified for cyst reduction may be used on disinfected water that may contain filterable cysts.