

9000 Series Retrofits

Application

- **Everpure® Systems**

Everpure is a registered trademark of Everpure, Inc.

Spec No. _____

Quantity _____



Product Features

- ◆ Specifically designed to fit in competitive systems to enhance performance and provide longer life.
- ◆ SQC™ - Sanitary Quick Change encapsulated design reduces contamination during change-outs and are disposable and incineratable.
- ◆ FDA CFR-21 and/or NSF compliant materials provide peace of mind that these products are suitable for potable applications.

CUNO's line of 9000 Series cartridges are an economical way to provide the benefits of CUNO filtration in competitive systems without incurring additional capital expense. A choice of medias such as graded density carbon with micron ratings from 0.5 to 5, as well as optional integrated scale inhibition provide solutions for varying water conditions. The 9000 Series cartridges do not require activation for functionality, allowing an operator to change the cartridge in seconds. Independent third party certification provides assurance that the cartridges will perform as expected*.

Product Specifications

Model Number	Part Number	Micron Rating	Chlorine Reduction, Hardness Capacity	Additional Claims	Flow Rate
CFS9110	55721-01	5	N/A	Sediment Reduction	1.5 gpm (5.7 lpm)
CFS9112	55892-03	1	10,000 gal. (37,854 lit.)	Sediment Reduction	1.5 gpm (5.7 lpm)
CFS9812X	56012-01	0.5	9,000 gal. (34,069 lit.)	Cyst Reduction	1.5 gpm (5.7 lpm)
CFS9720	55890-03	5	4,800 gal. (18,170 lit.)	Sediment Reduction	1.5 gpm (5.7 lpm)
CFS9110-S	55721-03	5	N/A	Sediment Reduction, Scale Inhibition	1.5 gpm (5.7 lpm)
CFS9112-S	55892-01	1	10,000 gal. (37,854 lit.)	Sediment Reduction, Scale Inhibition	1.5 gpm (5.7 lpm)
CFS9812X-S	56012-03	0.5	9,000 gal. (34,069 lit.)	Cyst Reduction, Scale Inhibition	1.5 gpm (5.7 lpm)
CFS9720-S	55890-01	5	4,800 gal. (18,170 lit.)	Sediment Reduction, Scale Inhibition	1.5 gpm (5.7 lpm)
CFS9710-S	55891-01	5	2,400 gal. (9,085 lit.)	Sediment Reduction, Scale Inhibition	1 gpm (3.8 lpm)
CFS9005-IMF	55937-01	N/A	N/A	Scale Inhibition	2 gpm (7.6 lpm)
CFS9110EL	55721-05	5	N/A	Sediment Reduction	1.67 gpm (6.3 lpm)
CFS9112EL	55892-13	1	12,600 gal. (47,696 lit.)	Sediment Reduction	1.67 gpm (6.3 lpm)
CFS9812ELX	56012-05	0.5	14,000 gal. (52,996 lit.)	Cyst Reduction	1.67 gpm (6.3 lpm)
CFS9720EL	55890-05	5	5,500 gal. (20,820 lit.)	Sediment Reduction	1.67 gpm (6.3 lpm)
CFS9110-ELS	55721-07	5	N/A	Sediment Reduction, Scale Inhibition	1.67 gpm (6.3 lpm)
CFS9112-ELS	55892-15	1	12,600 gal. (47,696 lit.)	Sediment Reduction, Scale Inhibition	1.67 gpm (6.3 lpm)
CFS9812ELX-S	56012-07	0.5	14,000 gal. (52,996 lit.)	Cyst Reduction, Scale Inhibition	1.67 gpm (6.3 lpm)
CFS9720-ELS	55890-07	5	5,500 gal. (20,820 lit.)	Sediment Reduction, Scale Inhibition	1.67 gpm (6.3 lpm)
SWC9135	55722-01	N/A	1,350 Grains	Scale Reduction	0.5 gpm (1.9 lpm)
SWC9135-C	55722-03	N/A	1,100 Grains	Scale Reduction, Chlorine Taste and Odor Reduction	0.5 gpm (1.9 lpm)

* For NSF listed products, visit www.nsf.org.



Water Filter Systems
Foodservice

9000 Series Replacements

Spec No. _____
 Quantity _____
 Model Number _____
 Part Number _____

Installation Tips:

- Shut off downstream equipment prior to installation of the system.
- Do not exceed operating parameters for temperature or pressure.
- Do not install outdoors.
- For cold water use only.
- For commercial use only.
- To have maximum operating pressure of 125 psi (862 kPa) and operating temperature of 100°F (38°C).

Cross Reference Guide

Standard

Model Number	Part Number	Replaces	Flow Rate
CFS9110	55721-01	CV	1.5 gpm (5.7 lpm)
CFS9112	55892-03	MC	1.5 gpm (5.7 lpm)
CFS9812X	56012-01	MC	1.5 gpm (5.7 lpm)
CFS9720	55890-03	MC/2CB5/4CB5	1.5 gpm (5.7 lpm)
CFS9110-S	55721-03	MH/I-2000	1.5 gpm (5.7 lpm)
CFS9112-S	55892-01	MH/I-2000	1.5 gpm (5.7 lpm)
CFS9812X-S	56012-03	MH/I-2000	1.5 gpm (5.7 lpm)
CFS9720-S	55890-01	MC/2CB5-S/4CB5-S	1.5 gpm (5.7 lpm)
CFS9710-S	55891-01	BH	1 gpm (3.8 lpm)
CFS9005-IMF	55937-01	IMF	N/A

Extended

Model Number	Part Number	Replaces	Flow Rate
CFS9110EL	55721-05	XCV	1.67 gpm (6.3 lpm)
CFS9112EL	55892-13	MC/XC	1.67 gpm (6.3 lpm)
CFS9812ELX	56012-05	MC/XC	1.67 gpm (6.3 lpm)
CFS9720EL	55890-05	4CB5/7CB5	1.67 gpm (6.3 lpm)
CFS9110-ELS	55721-07	MH/I-4000	1.67 gpm (6.3 lpm)
CFS9112-ELS	55892-15	MH/I-4000	1.67 gpm (6.3 lpm)
CFS9812ELX-S	56012-07	MH/I-4000	1.67 gpm (6.3 lpm)
CFS9720-ELS	55890-01	4CB-5-S/7CB-5-S/I-4000	1.67 gpm (6.3 lpm)
SWC9135	55722-01	7SO	0.5 gpm (1.9 lpm)
SWC9135-C	55722-03	7SO	0.5 gpm (1.9 lpm)

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts. EPA Establishment Number 070595-CT-001.

CUNO Incorporated recommends regularly scheduled maintenance and replacement of the filter cartridge(s) in order for the product to perform as advertised/sold.

Service Worldwide

China
 CUNO Filtration Shanghai Co. Ltd.
 No. 2 Plant East Side
 Xin Miao San Road
 XinQiao Town SongJiang District
 Shanghai, China 201612

Australia
 CUNO Pacific Pty Ltd.
 140 Sunnholt Road
 Blacktown, N.S.W. 2148
 Australia

Europe
 CUNO Limited
 21 Woking Business Park
 Albert Drive
 Woking, Surrey
 GU21 5JY, England



Japan
 CUNO K.K.
 Hodogaya Station Building 6F
 1-7, Iwai-Cho, Hodogaya-Ku
 Yokohama 240-0023, Japan

Brazil
 CUNO Latina Ltda
 Rua AMF do Brazil - 251
 18120 Mairinque-SP, Brazil

Singapore
 CUNO Filtration Asia Pte Ltd
 18 Tuas Link 1
 3rd Floor
 Singapore 638599

CUNO Incorporated
 400 Research Parkway
 Meriden, CT 06450, USA
 Toll Free: 1-888-218-CUNO
 Worldwide: 203-237-5541
 Fax: 203-238-8701