

DEV9108-25

CG5-20 Replacement Cartridge

Drop-in Replacement Cartridge for Foodservice Applications

BENEFITS

Five micron carbon block reduces dirt and fine particles from drinking water

Effectively reduces unwanted tastes, odor and chlorine

High porosity design prevents the cartridge from plugging before its adsorption capacity is

Improves the taste of beverages such as fountain drinks and coffee

Helps keep equipment running at peak efficiency and keeps maintenance costs down

Drop-in design fits most 20" bowls

CG5-20 Replacement Cartridge: DEV9108-25

INSTALLATION TIPS

Install vertically so bowls hang down.

Allow 2-I/2" clearance below the cartridge for easy cartridge replacement

Make sure O-ring on bowl is sufficiently lubricated

Always screw on bowls by hand; do not use a housing wrench

OPERATION TIPS

Change cartridges on a regular 6 month preventative maintenance program

Change cartridges when capacity is reached or when pressure decreases

Always inspect O-ring; change and/or lubricate if necessary

Always flush the filter cartridge at time of installation and cartridge change

APPLICATION/SIZING

For foodservice applications

Drop-in cartridge for taste, odor and sediment reduction

Capacity: 12,000 gallons (45,400L)

SPECIFICATIONS

Overall Dimensions: 20"H x 2.87" Diameter

Service Flow Rate: Maximum 3.34 gpm (7.6 Lpm)


Pressure Requirements: 30 - 125 psi (2.1 – 8.6 bar), non-shock

Temperature: 40 - 100°F (4.4 - 38°C)

No electrical connection required

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

CG5-20 Replacement Cartridge



WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



System Tested and Certified by NSF International against NSF/ANSI Standard 42 for the reduction of:

Standard No. 42: Aesthetic Effects Chemical Unit Taste and Odor Reduction Chlorine Reduction



EVERPURE, LLC 1040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323-7873 Tel (630) 307-3000 Fax (630) 307-3030 http://www.everpure.com In Europe: N.V. EVERPURE (EUROPE) S.A. Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals Belgium

Tel 32 -14-283500 Fax 32-14-283505 In Japan:
EVERPURE JAPAN LLC
HASHIMOTO MN BLDG. 7F
3-25-1 HASHIMOTO SAGAMIHARA-SHI
KANAGAWA 229-1103
JAPAN
TEL 81-(0)42-775-3011
FAX 81-(0)42-775-3015

Everpure, LLC 1040 Muirfield Drive Hanover Park, IL 60133

Phone: 630-307-3020 Fax: 630-307-3030