

Operating Specifications:

Maximum operating temperature... 38°C/100°F

Minimum operating temperature.... 0.6°C/33°F

Max. working pressure689 kPa/100 psi

Min. working pressure..... 140 kPa/20 psi

Rated capacity* 1,325 litres/350 gallons

Flow rate* 1.9 lpm/0.5 gpm

Replace every 6-8 months

*Tested by an independent laboratory.

Estimated % reduction

Lead Reduction*	95%
Cysts Reduction*	99%
Chlorine Taste & Odor Reduction*	95%
Turbidity Reduction*	95%
Asbestos Reduction*	95%
Atrazine Reduction*	95%
Alachlor Reduction*	95%
Lindane Reduction*	95%
2,4-D Reduction*	95%
Mercury Reduction*	95%
Toxaphene Reduction*	95%
P-Dichlorobenzene Reduction*	95%
Benzene Reduction*	95%

NSF/ANSI 42 by



COMPONENT

This model is tested and Certified by WQA according to NSF/ANSI Standard 42 for material requirements only.

- This filter keeps a healthy level of fluoride, a water additive that promotes strong teeth. Applies to fluoridated municipal tap water.
- This filter is not intended to purify water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.
- The substances removed or reduced by this water treatment device are not necessarily in all users' water.
- Reminder: Flush filter for 3 minutes (approx. 10 glasses) for optimal performance.
- It is normal to see sputtering, intermittent or slow flow during the first 3 minutes.