

Installation instruction:

1. Unlatch the plastic filter cover, and let it swing down
2. Twist the old filter a quarter-turn counterclockwise
3. Pull the filter straight out and discard
4. Push the new filter into the fridge until it stops
5. Twist the filter a quarter-turn clockwise
6. Swing the plastic filter cover up until it snaps closed
7. Reset your "change filter" light (if your fridge has one)

Operating Specifications:

Minimum operating temperature.....	0.6 °C/33 °F
Maximum operating temperature.....	38 °C/100 °F
Min.working pressure.....	140 kPa/20 psi
Max.working pressure.....	827 kPa/120 psi
Rated capacity.....	2,839 litres/750 gallons
Flow rate.....	1.9 lpm/0.5 gpm

A replacement for the following refrigerator water filters:**Amana®/Maytag®**

- UKF8001AAXX, UKF8001AAX-750
- UKF8001,8001P,UKF8001AAXXP
- UKF9001,UKF9001AAXX
- WF50, OWF50, WF51, OWF51
- WF50-NI300,OWF50-NI300
- WF50-KNI300
- WF50-NI500,OWF50-WI500
- WF50-WI500,WF50-KWI500
- 67002269,67002671,67003523
- 67003526,67003527,67003528
- 67003591,67003727,67006474
- 67006637
- 12589201,12589203,12589206
- 12589208,12589210

kitchenAid®

- 4396395,8171032,8171249

Sears®/Kenmore®

- 46-9005,469005,9005,9005P
- 46-9006,469006,9006,9006P
- 46-9992,469992,9992,9992P
- 469005750,469005-750,46-9005-750
- 469006750,469006-750,46-9006-750
- 04609005000,04609006000

Filter features:

- Provide cleaner, fresher water by reducing impurities.
- High quality, cost-effective alternative to factory original.
- Easy installation and operation.
- All materials are tested and certified against ANSI/NSF Standard.