	EV9275-70 QL2-OW200L Sys	stem <u>s</u> C
Delivers premium quality drinking drinking fountains	water for bottleless coolers and	
<image/>	QL2-OW200L System: EV9275-70 OW200L Replacment Cartridge: EV9619-01	BENEFITS   Provides sparkling, fresh, premium quality drinking water   Everpure's unique filter blend using activated carbon reduces chlorine taste and odor and other offensive contaminants   Reduces lead to below the Federal Action Level of 10 ppb   Effectively reduces Trihalomethanes (TTHMs)   Precoat submicron technology reduces dirt and particles as small as 1/2 micron in size   Reduces possible health contaminants such as asbestos fibers and Cryptosporidium and Giardia cysts   Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination   Features quick release head without shut- off   NSF Certified under NSF/ANSI Standards 42 and 53
<b>INSTALLATION TIPS</b> Never use saddle valve for connection Use 3/8" water line Install vertically with cartridge hanging down Allow 2-1/2" clearance below the cartridge for easy cartridge replacement Flush OW200L cartridge by running water through filter for three minutes at full flow	OPERATION TIPS   Change cartridges on a regular 6 month preventative maintenance program   Change cartridges when capacity is reached or when pressure falls below to psi   Service flow rate must not exceed 0.5 gpm   Always flush the filter cartridge at time of installation and cartridge change	APPLICATION/SIZING   For office water applications   Bottleless water coolers and drinking fountains   Rated Capacity: 480 gallons (1,816 L)

## QL2-OW200L System

## S P E C I F I C A T I O N S

Overall Dimensions: 19"H x 4.25"W x 4"D

Inlet connection: 3/8"

Outlet connection: 3/8"

Service Flow Rate: Maximum 0.5 gpm (1.9 Lpm)

Rated Capacity: 480 gallons

Pressure Requirements: 10 - 125 psi (0.7 – 8.6 bar), non-shock


Maximum Temperature: 35 - 100°F (2 - 38°C)

No electrical connection required

Shipping Weight: 4 lbs.

Operating Weight: 6 lbs.

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.



## WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



System Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of:

Standard No. 42: Aesthetic Effects Chemical Unit Taste and Odor Reduction Chlorine Reduction Mechanical Filtration Unit Particulate Reduction, Class I: 99.9+% reduction of particles one-half micron and larger in size

Standard No. 53: Health Effects Chemical Reduction Unit Lead Reduction TTHM Reduction Mechanical Filtration Unit Cyst Reduction



Worldwide Headquarters: EVERPURE, LLC 1040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323-7873 Tel (630) 307-3030 http://www.everpure.com In Europe: Pentair Water Belgium B.V./B.A. Industriepark Wolfstee Toekomstdaan 30 B-2200 Herentals BELGIUM TEL: +32.(0).14.283,500 FAX: +32.(0).14.283,505 In Japan: Hashimoto MN Bldg. 7F 3-25-1 Hashimoto Sagamihara-Shi Kanagawa 229-1103 JAPAN TEL: 81.(0)42.775.3011 FAX: 81.(0)42.775.3015

Everpure 1040 Muirfield Drive Hanover Park, IL 60133