



Cabin Air Filter Product: MicronAir® No. HY99171P

1

- **SONATA:** OPEN THE GLOVE COMPARTMENT. PRESS INWARD AT BOTH SIDES OF THE GLOVE COMPARTMENT, THEN LOWER THE GLOVE COMPARTMENT.
- **XG:** OPEN THE HOOD. REMOVE THE GLOVE COMPARTMENT STOP, THEN LOWER THE GLOVE COMPARTMENT.

2

- **SONATA:** REMOVE THE LOWER SIDE INSTRUMENT PANEL CRASH TRIM PAD. REMOVE THE FOUR GLOVE COMPARTMENT UPPER COVER RETAINING SCREWS, THEN THE COVER. REMOVE THE TWO GLOVE COMPARTMENT RETAINING BOLTS, THEN THE GLOVE COMPARTMENT. PRESS ON THE CABIN AIR FILTER COVER TAB, THEN REMOVE THE COVER.
- **XG:** REMOVE THE TWO GLOVE COMPARTMENT ATTACHING BOLTS AND TWO ATTACHING SCREWS, THEN THE GLOVE COMPARTMENT. REMOVE THE RIGHT LOWER SIDE INSTRUMENT PANEL CRASH TRIM PAD. DISCONNECT THE LUGGAGE COMPARTMENT LAMP ELECTRICAL CONNECTOR. PUSH DOWNWARD ON THE BLOWER UNIT UNDER COVER, THEN REMOVE THE COVER.

3

- ▮ **SONATA:** REMOVE THE CABIN AIR FILTER FROM THE BLOWER UNIT OPENING. INSTALL A NEW MICRONAIR® CABIN AIR FILTER, ENSURING AIR FLOW MARKING IS FACING IN THE PROPER DIRECTION. INSTALL THE CABIN AIR FILTER COVER, ENSURING THE COVER IS PROPERLY INSTALLED.
- ▮ **XG:** REMOVE THE CABIN AIR COVER; REMOVE THE FILTER FROM THE BLOWER UNIT OPENING. INSTALL A NEW MICRONAIR® CABIN AIR FILTER, ENSURING AIR FLOW MARKING IS FACING IN THE PROPER DIRECTION. INSTALL THE CABIN AIR FILTER COVER, ENSURING THE COVER IS PROPERLY INSTALLED. INSTALL BLOWER UNIT UNDER COVER. CONNECT THE LUGGAGE COMPARTMENT LAMP ELECTRICAL CONNECTOR.

4

- **SONATA:** POSITION THE GLOVE COMPARTMENT TO THE INSTRUMENT PANEL, THEN INSTALL THE TWO RETAINING BOLTS. INSTALL THE GLOVE COMPARTMENT UPPER COVER. INSTALL THE LOWER SIDE INSTRUMENT PANEL CRASH PAD. LIFT THE GLOVE COMPARTMENT INTO POSITION. CLOSE THE GLOVE COMPARTMENT.
- **XG:** POSITION THE GLOVE COMPARTMENT TO THE INSTRUMENT PANEL, THEN INSTALL THE TWO RETAINING BOLTS. INSTALL THE GLOVE COMPARTMENT UPPER COVER. INSTALL THE RIGHT LOWER SIDE INSTRUMENT PANEL CRASH TRIM PAD. INSTALL THE LOWER SIDE INSTRUMENT PANEL CRASH PAD. POSITION THE GLOVE COMPARTMENT TO THE INSTRUMENT PANEL, THEN INSTALL THE TWO GLOVE COMPARTMENT ATTACHING BOLTS AND TWO ATTACHING SCREWS. LIFT THE GLOVE COMPARTMENT INTO POSITION AND INSTALL THE STOP. CLOSE THE GLOVE COMPARTMENT.

**This MicronAir® Cabin Air Filter fits: Hyundai Sonata, model years 1999-2005;
and Hyundai XG, from model year 2001.**

Get in and breathe easy.

THE VEHICLE MANUFACTURER RECOMMENDS THAT THE FILTER BE CHANGED EVERY YEAR OR 15,000 MILES.
ENGINEERED FOR ORIGINAL EQUIPMENT MANUFACTURER SPECIFICATIONS.

www. .com

908546 REV. A 42