2-Year Warranty

COMFORT CONTROL CONVENIENCE



Energy STAR

Climatouch[™] is a true touch-screen operated thermostat with an intuitive graphic user interface. Its revolutionary features and environmental comfort controls are conveniently accessible with the touch of a finger. Climatouch[™] makes it possible to easily configure and operate any HVAC system with simplicity and precision.

Construct



www.climatouch.com

Climatouch[™] TECHNICAL SPECIFICATIONS

CTO-7TC-21 » 2 Heating and 1 Cooling

Perfect for many straightforward residential and commercial installations.

CTO-7TC-32 » 3 Heating and 2 Cooling

The ideal choice for multi-stage installations – also can be used with a HRV or ERV, providing convenience and comfort in one thermostat.

CTO-7TC-32H » 3 Heating and 2 Cooling with Humidistat

Climatouch[™] is the only true touch screen thermostat equipped with a humidity sensor and controller, providing control convenience in one package. 2 separate configurable relays provide control of humidification or de-humidification, maximizing home comfort.

Humidify - Enables fan for steam type humidifiers, disables fan for drum type humidifiers. **De-humidify** - Variable fan-speed de-humidification or control a separate de-humidifier.

CTO-7TC-32AD» 3 Heating and 2 Cooling with Humidistat featuring Automatic Humidity Control and Dual Fuel Switch

Automatic Humidity Control - Outdoor temperature is measured and transmitted to the thermostat, indoor humidity and temperature information is measured utilizing state of the art humidity and temperature sensors located within the thermostat. Using a humidity algorithm the environment is effectively maintained, eliminating destructive condensation problems and maintaining a higher level of comfort. This feature can only be used in conjunction with the Wireless Outdoor Temperature Transmitter and Receiver Kit.

Automatic Fossil Fuel Switch - Dual Fuel Capacity - This Advanced Settings feature allows the installer to set an outdoor temperature set point (between +13°F to +41°F). When the outdoor set point temperature is reached the thermostat will automatically divert any call to heat pump to the AUX heat system. This feature can only be used in conjunction with the Outdoor Wireless Temperature Transmitter and Receiver Kit.

CTO-7TC-2W » 2 Heating and 1 Cooling with HVAC Control Board – 2 Wire

The solution for after market installations where a common wire is not available – compatible with hydronic and zone systems. Perfect for use on hot water/boiler systems, oil or gas furnaces.

90064

» Wireless Outdoor Temperature Transmitter and Receiver Kit

Accurately displays outdoor temperature on the Climatouch[™] thermostat. Robust 915 MHz spread spectrum technology ensures accurate transmission between the Transmitter and the Receiver.

The kit includes:

- » Wireless Outdoor Temperature Transmitter
- » Antenna
- » Receiver Module
- 2 Batteries





Gas, Oil, Electric, Heat Pump, Air Conditioning and Multistage HVAC Systems (3 heating + 2 cooling)

2 cooling)	
Single Stage Heating and Cooling	V
Multistage Heating and Cooling	V
Heating Only	V
Cooling Only	V
Furnace (Warm Air)	V
Central Air Conditioning	V
Heat Pump with Auxiliary Heat	V
Heat Pump without Auxiliary Heat	V

Physical Dimensions

Case: 5.75" x 4.75" x 1.25" (145mm x 120mm x 30mm) Display: 3.625" x 2.125" (95mm x 55mm)

Electrical Rating

24 volt AC/DC Class 2 maximum 4 amps Temperature Accuracy +/-1°F degree Humidity Accuracy +/- 5%RH

Patents

7,058,477; 7,050,026; 7,028,912; 6,902,117; 6,824,069; 6,789,739; 6,786,421; 6,619,555; 6,581,846; Other Patents Pending





FCC ID: RAN 90064 FCC ID: RAN 90164fcc INDUSTRY CANADA IC: 2294A-90064 INDUSTRY CANADA IC: 2294A-90164



AED Electronics Inc. 5758 Royalmount Avenue, Montreal, QC, H4P 1K5, Canada TEL (514) 737-9332 FAX (514) 737-0922

www.climatouch.com

