## micronAir®

## Cabin Air Filtration Product MicronAir<sup>®</sup> No. NN00192P, NN00192C



- A. Remove the lower glove box trim panel (3 clips).
- B. Open the glove box and remove the glove box latch (2 screws)
- C. Remove the glove box (4 Screws) and remove the glove box light.
- D. Carefully remove the yellow airbag connector by releasing the two push-in fasteners retaining it to the glove box.

(Hint: Squeeze the side prongs together with needle nose pliers)

\*\*Caution\*\* DO NOT DISCONNECT THE YELLOW AIRBAG CONNECTORS FROM EACH OTHER!

- 2
- A. Remove the filter cover by removing the retaining clip.
- B. Remove the used cabin filters noting the installation direction.
- C. Install the new micronAir® cabin air filters into the housing.



- A. Replace the filter cover and attach the clip.
- B. Attach the airbag connector to the glove box. Make sure that the two push-in fasteners are properly secured, and then snap the glove box flap for the connector back into the locked position.
- C. Replace the glove box light.
- D. Install the glove box, latch, and trim panel.

This micronAir<sup>®</sup> Cabin Filter fits: Nissan Maxima, Infiniti 130/135

## Get in and breathe easy.

The vehicle manufacturer recommends that the filter be changed every year or 15,000 miles. Engineered for Original Equipment Manufacturer Specifications.

