

# NP-3MM30

## SQC RO Membrane Compatible Replacement Cartridges

**neo·PURE**<sup>®</sup>  
Filtration Products



Component  
NP-3MM30 is tested  
and certified by WQA  
to NSF/ANSI 372 and  
NSF/ANSI 58 for  
material safety and  
structural integrity  
requirements



### Residential/Commercial Filtration Applications

### Standard Features

- Manufactured in South Korea
  - Formally NP-SQCM30
  - Compatible with the Water Factory Systems SQC3 and SQC4 systems
  - Replacement for 3MROM413, OWS33-RO, 5598718, 55987-18, 66-4706G2, 66-4706CM, 66-4703G2, 4373501, PSQC-5\*
  - Reduces chlorine taste and odor, and sediment, dirt, rust, cysts and VOCs
  - Quick change design for easy installation
  - NP-3MM30 is tested and certified by WQA to NSF/ANSI 372 and NSF/ANSI 58 for material safety and structural integrity requirements
- \*Not tested by WQA in these systems

### Product Specifications

#### Flow Rate

0.6 gpm or 30 GPD

#### Operating Temperature

34 to 100 °F (4.4 to 37.8 °C)\*

#### Operating Pressure

30 -120 psi

#### Change Frequency

24-36 months

#### Capacity

2500 Gallons

#### Materials of Construction

Filter Media: TFC (Thin Film Composite)

\*Temperature ratings vary and depend on pressure and time under load

### Contaminants Reduced:

- Chlorine Taste and Odor
- Dirt
- Rust
- Sediment
- Cysts
- VOCs

Distributed

**neoLogic**  
solutions  
filtration division

2299 Ridge Rd., Greenville, SC  
P: 888.859.1188 • F: 864.284.1819  
[NeoLogicSolutions.com](http://NeoLogicSolutions.com) • [Info@NeoLogicSolutions.com](mailto:Info@NeoLogicSolutions.com)

### Questions?

Ask our Service Representatives at:  
888.859.1188 Mon.-Fri. 8a-8p,  
Sat 8:30a-4:30p EST.