

NP217

Water Filter Replacement Cartridge



Contaminants Reduced

- 1 Sediment
- 2 Chlorine Taste and Odor

Residential / Commercial Filtration Applications

Standard Features

- Granular activated carbon (GAC) filter
- Two-stage water filter; first stage uses a graded density prefilter; second stage passes water through granular activated carbon where unwanted tastes, odors and chlorine are reduced
- Compatible with Aqua-Pure® AP217; also fits Aqua-Pure® AP200 and Purwater® PW-200
- Drop-in cartridge style
- Manufactured with FDA CFR-21 compliant materials

Product Specifications

Dimensions

3-3/8" OD x 7" (17.8 cm)

Filter Media

Granular activated carbon (GAC)*

Chlorine Capacity

2,000 gallons @ 2.0 GPM

Operating Temperature

40 to 100° F (4.4 to 37.8° C)

Operating Pressure

425 to 125 psi

Maximum Flow Rate

2 gpm

Micron Rating (Nominal)

5 micron

Change Frequency

6 to 12 months

WARNING:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Distributed By:



2299 Ridge Rd., Greenville, SC
P: 888.859.1188 · F: 864.284.1819
NeoLogicSolutions.com · Info@NeoLogicSolutions.com

Questions?

Ask our Service Representatives at:
888.859.1188 Mon.-Fri. 8a-8p,
Sat 8:30a-4:30p EST.

* Temperature ratings vary and depend on pressure and time under load.
All rights and illustrations reserved. Manufacturer reserves the right to make changes without notice. ©2017 NeoLogic Solutions.