

Performance Data Sheet


Manufacturer: Electrolux Home Products
Product: SCWF5CTO-S

Testing Conditions:

Flow Rate: 0.5 gpm (1.9 Lpm) pH: 7.5 ± 0.5
Inlet Pressure: 60 psi (4.1 bar) Temp: 50 – 77 °F (10 – 25 °C)

Operating Requirements:

Rated Service Life: 300 gallons (1,136 Liters)
Pressure Range: 25 – 80 psi (172-552 kPa)
Rated Service Flow: .5 gpm at 60 psi (1.9 Lpm at 4.1 bar)
Temperature Range: 34 –100°F (1 – 38°C)



System certified by IAPMO R&T to NSF/ANSI 42 for the reduction of Chlorine and NSF/ANSI 372 for Low Lead content.

Substance Reduction:

While testing was performed under standard laboratory conditions, actual performance may vary.

Substance	Influent Challenge Water Concentration	Reduction Requirements	Actual Average % Reduction
Chlorine	2.0 mg/L ± 10%	≥ 50%	89.56

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

The replacement filter is SCWF5CTO which can be found at DiscountFilters.com. The disposable filter cartridge must be changed every 6 months or 300 gallons (whichever comes first). Failure to replace the disposable filter cartridge may lead to reduced filter performance and cracks in the filter housing causing water leakage, flooding or property damage. Flush at least 5 gallons of water through filter cartridge before use. Refer to the product manual for more specific product information, installation instructions, and instructions on replacing the filter cartridge.

Limited Warranty:

Electrolux Home Products warrants our water filters to be free from defects in materials and workmanship for a period of 6 months from date of purchase.

Contact Information: Electrolux Home Products; 10200 David Taylor Drive, Charlotte, NC 28262; Phone 888-407-5688