

Max. working pressure ..... 689 kPa/100 psi  
 Min. working pressure..... 140 kPa/20 psi  
 Rated capacity\* ..... 1,137 litres/300 gallons  
 Flow rate\* ..... 1.9 lpm/0.5 gpm  
 Replace every 6-8 months  
 \*Tested by an independent laboratory.  
 Estimated % reduction

Lead Reduction*	95%
Cysts Reduction*	99%
Chlorine Taste & Odor Reduction*	95%
Turbidity Reduction*	95%
Asbestos Reduction*	95%
Atrazine Reduction*	95%
Alachlor Reduction*	95%
Lindane Reduction*	95%
2,4-D Reduction*	95%
Mercury Reduction*	95%
Toxaphene Reduction*	95%
P-Dichlorobenzene Reduction*	95%
Benzene Reduction*	95%

NSF/ANSI 42 by



**COMPONENT**

This model is tested and Certified by WQA according to NSF/ANSI Standard 42 for material requirements only.

This filter keeps a healthy level of fluoride, a water additive that promotes strong teeth. Applies to fluoridated municipal tap water.

This filter is not intended to purify water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

The substances removed or reduced by this water treatment device are not necessarily in all users' water.

Reminder: Flush filter for 3 minutes (approx. 10 glasses) for optimal performance.

It is normal to see sputtering, intermittent or slow flow during the first 3 minutes.