

PERFORMANCE DATA SHEET
Ice & Water Filter System

APPLICATION GUIDELINES / CONDITIONS OF USE

Water Supply	Municipal or well applications
Water Temp.	Max. 100°F (38°C), Min. 33°F (0.6°C) - For cold water use only
Water Pressure	100 psi Max. 30 psi Min., as measured at the valve inlet
<ul style="list-style-type: none"> Timely cartridge replacement is essential for the product to perform as advertised. Please refer to the Use & Care Guide for general operation and maintenance requirements. Refer to the Use & Care Guide for complete instructions. Flush new cartridge for 4 minutes. Should not be used on water that is microbiologically unsafe or with water of unknown quality without adequate disinfection before or after the system. While testing was performed under standard laboratory conditions, actual performance may vary based on local water conditions and/or pressure. High sediment areas may require more frequent filter cartridge replacement. System will absorb bad tastes and odors in both ice cubes and drinking water. 	


SYSTEM SPECIFICATIONS

Flow Rate	Dispenser - 64 oz per minute (0.5 gpm or 1.89 liters per minute) at 60 psi (as measured at valve inlet)
Capacity	200 gallons (757 liters)
System Construction	Filter Housing Assembly - Polypropylene Plastic Tubing - Polyethylene Plastic Filter Media - Extruded Carbon block

REPLACEMENT CARTRIDGE INFORMATION

Replacement SCWF3CTO cartridges are available by calling the Customer Assistance Center at 1-800-599-7569. Please reference installation instructions in the Use & Care Guide for replacing the cartridge and warranty information. Estimated cost for the replacement filter cartridge kit: Less than \$40.00.

PERFORMANCE DATA

	The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 42.				
General test water parameters: pH = 7.5 +/- 0.5 Temp. 20°C +/- 3°C (68°F +/- 5°F) Pressure = 60 psi					
Substance Reduction	NSF Standard	NSF Reduction Requirements	Influent Challenge Concentration	Max. Permissible Product Water Concentration	Average % Reduction
Chlorine, Taste & Odor	42	>= 50%	2.0 ± 10% mg/L	NA	97.30%

