



Performance Data Sheet

Replacement Element: RC-900 (without Performance Indicator) or WFCB (with Performance Indicator)

For Use with Models: NGRG2000 (w/out PID) and NGRG2000 (w/PID)

The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system as specified in NSF/ANSI Standard 42 and Standard 53.

System tested and certified by NSF International against NSF/ANSI Standard 42 and Standard 53 for the reduction of substances listed below.

Capacity: RC-900 - 200 Gallons (757 Liters)
WFCB - 400 Gallons (1514 Liters)
Contaminant Reduction Determined by NSF testing.

Contaminant Reduction	Average Influent	NSF/ANSI Specified Challenge Concentration	Avg % Reduction	Average Product Water Concentration	Max Permissible Product Water Concentration	NSF Reduction Requirements	NSF Test Report
Chlorine Taste and Odor	2.0 mg/L	2.0 mg/L ± 10%	97.5%	0.05 mg/L	N/A	≥ 50%	J-00068311
Nominal Particulate Class I, ≥0.5 to < 1.0 µm	9,866,667 pts/mL	At least 10,000 particles/mL	99.7%	20,633 pts/mL	N/A	≥85%	J-00068313
Cyst*	127,500 cysts/L	Minimum 50,000 cysts/L	99.99%	1 cyst/L	N/A	≥99.95%	J-00068317
Turbidity	11 NTU	11 ± 1 NTU	99%	0.1 NTU	0.5 NTU	N/A	J-00068319
Lead @ pH 6.5	0.15 mg/L	0.15 mg/L ± 10%	99.3%	0.001 mg/L	0.010 mg/L	N/A	J-00068321
Lead @ pH 8.5	0.15 mg/L	0.15 mg/L ± 10%	99.3%	0.001 mg/L	0.010 mg/L	N/A	J-00068324
Atrazine	0.009 mg/L	0.009 mg/L ± 10%	94.1%	0.5 mg/L	0.003 mg/L	N/A	J-00068326
2, 4-D	0.212 mg/L	0.210 mg/L ± 10%	99.8%	0.0002 mg/L	0.07 mg/L	N/A	J-00068354

* Based on the use of Cryptosporidium parvum oocysts

Application Guidelines/Water Supply Parameters	
Service Flow	0.5 gpm (1.9 lpm)
Water Supply	Potable Water
Water Pressure	30-100 psi (207 – 689 kPa)
Water Temperature	33° F - 100° F (0.6° C - 38° C)

It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See Installation Manual for Warranty information.

Note: While the testing was performed under standard laboratory conditions, actual performance may vary.

Replacement Cartridge: RC-900 (without Performance Indicator) and WFCB (with Performance Indicator) available through local Electrolux dealer by calling the Consumer Assistance Center. For estimated costs of replacement elements please call at 1-800-944-9044 or visit our website at www.electrolux.com

⚠ WARNING

To reduce the risk associated with ingestion of contaminants:

- Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before and after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

EPA Establishment Number 070595-MEX-001

CAUTION

To reduce the risk associated with property damage due to water leakage:

- Read and follow Use Instructions before installation and use of this system.
- Installation and use **MUST** comply with all state and local plumbing codes.
- Do not install if water pressure exceeds 100 psi (689 kPa). If your water pressure exceeds 80 psi, you **must** install a pressure limiting valve. Contact a plumbing professional if you are uncertain how to check your water pressure.
- Do not install where water hammer conditions may occur. If water hammer conditions exist you **must** install a water hammer arrester. Contact a plumbing professional if you uncertain how to check for this condition.
- Do not install on hot water supply lines. The maximum operating water temperature of this filter system is 100° F (38° C).
- Protect filter from freezing. Drain filter when temperatures drop below 33°F (0.6°C).
- The disposable filter cartridge **must** be replaced every 6 months, at the rated capacity or if a noticeable reduction in flow rate occurs.

Electrolux Home Products
P.O. Box 212378
Augusta, GA 30907
Toll Free: 1-800-944-9044
www.electrolux.com