	EV9100-79 IN-10 UV In-line	Filter
	<image/>	BENEFITS 1/2 GPM UV module destroys bacteria and viruses using ultraviolet light 10" in-line design is compact and installs out of sight behind equipment
Uses 120/60 volts	OPERATION TIPS Replace UV cartridge every 12 months	A P P L I C A T I O N / S I Z I N G For drinking water applications Capacity: 12 months

IN-10 UV In-line Filter

S P E C I F I C A T I O N S

Overall Dimensions:

Length: 10"

Diameter: 2.0"

Inlet connection: 1/4"

Outlet connection: 1/4"


Service Flow Rate: Maximum 0.75 gpm (2.8 Lpm)

Pressure Requirements: 10 - 125 psi (0.7 – 8.6 bar), non-shock

Temperature: 35 - 100°F (2 - 38°C)

Operating Weight: 2.0 lbs.

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.



WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



EVERPURE, LLC 1040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323-7873 Tel (630) 307-3000 Fax (630) 307-3030 http://www.everpure.com In Europe: N.V. EVERPURE (EUROPE) S.A. Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals Belgium Tel 32 -14-283500 Fax 32-14-283505

In Japan: EVERPURE JAPAN LLC Hashimoto MN Bldg. 7F 3-25-1 Hashimoto Sagamihara-Shi Kanagawa 229-1103 Japan Tel 81-(0)42-775-3011 Fax 81-(0)42-775-3015

Everpure, LLC 1040 Muirfield Drive Hanover Park, IL 60133 Ph: 630-307-3000 Fax: 630-307-3030