



LiteBox® Rechargeable Lantern

Case Material: High-impact ABS thermoplastic housing. Rubberized impact bumper, lens ring and cushioned-grip handle.

Dimensions: Length: 11 .5 in. (29.2 cm) Width: 5.1 in. (13 cm) Height: 7 in. (17.8 cm)

Weight: 7.4 lbs (3.36 kg)*

Light Source: High-intensity halogen bi-pin bulb available in 8 watt and 20 watt spot and flood PAR 36 assembly. Xenon dual filament 8 watt safety bulb features instant backup beam.

Light Output:	Peak Beam Candlepower (Maximum)	Bulb Lumens (Typical)
<i>Bi-pin bulb:</i>		
8 watt flood	1,500	150
20 watt flood	3,000	400
8 watt spot	80,000	150
20 watt spot	105,000	400
<i>Dual Filament:</i>		
8 watt spot	70,000 each	157



Battery/Run Time: Zero-maintenance 6V, 12Ah sealed lead acid operates up to nine hours per charge and is rechargeable up to 500 times. Red and green LEDs give charge status feedback.

Models: Standard System - International safety orange or high-visibility yellow; includes shoulder strap; comes with AC and DC chargers and charge rack; ideal for field maintenance, inspection of construction sites, and remote equipment.

Vehicle Mount System - International safety orange or high-visibility yellow; comes with vehicle-mountable hard-wire rack and shoulder carrying strap.

Power Failure System - International safety orange or beige; comes with AC/DC chargers and "smart" power failure circuitry that automatically goes on when the power goes off.

Dual Filament System - International safety orange or high visibility yellow; features backup 8 watt safety spot; includes shoulder strap.

Approvals**: Most models meet applicable European Community Directives.
Rack meets requirements of NFPA 1901-12-1.7 mounted in any position.

Warranty: Limited lifetime warranty.

- Optional
- 100V, 120V, or 240V AC (home) and 12V DC (automobile) charger cords.
- Accessories:
- Hands-free shoulder strap (included in Standard & VM models)
 - Locking charge rack
 - Dual filament bulb offering instant backup available on Standard and Vehicle Mount systems
 - Quick release shoulder/waist strap

*With battery (included in purchase).

**See product for specific ratings.

LiteBox Standard System		
Standard System	Yellow	#45117 (8WS)
Standard System	Yellow	#45109 (20WS)
Standard System	Yellow	#45113 (20WF)
Standard System	Orange	#45116 (8WS)
Standard System	Orange	#45110 (20WS)
Standard System	Orange	#45111 (20WF)

LiteBox Dual Filament Standard System		
Dual Filament Stdrd System	Yellow	#45705 (8WS)
Dual Filament Stdrd System	Orange	#45704 (8WS)



LiteBox Vehicle Mount System		
Vehicle Mount System	Yellow	#45108 (8WS)
Vehicle Mount System	Yellow	#45104 (20WS)
Vehicle Mount System	Orange	#45107 (8WS)
Vehicle Mount System	Orange	#45102 (20WS)



LiteBox Power Failure System		
Power Failure System	Orange	#45131 (8WS)
Power Failure System	Orange	#45127 (8WF)
Power Failure System	Beige	#45133 (8WS)
Power Failure System	Beige	#45129 (8WF)



Locking device (keyed alike, #525)		#40164
Locking device (keyed different)		#40163
Shoulder Strap		#45232
Mounting Rack	Yellow	#45072
Mounting Rack	Orange (not shown)	#45070
Mounting Rack	Beige (not shown)	#45073
12V DC Mounting Rack	Orange (not shown)	#45071
12V DC Mounting Rack	Yellow (not shown)	#45074
8 Watt Spot Lamp Assembly **		#45911
20 Watt Spot Lamp Assembly **		#45913
8 Watt Flood Lamp Assembly**		#45908
20 Watt Flood Lamp Assembly**		#45910
8 Watt Bi-Pin Bulb (100 hr)		#45901
Battery		#45937

**Examples of one spot and one flood lamp assembly shown for representation



120V AC charge cord	#22311
12V DC cigarette lighter charge cord	#22051
12V DC direct wire charge cord	#22050



Quick Release Strap	#44050
---------------------	--------