



## Survivor® Division 2 Flashlight

**Case Material:** Lamp housing, battery housing and battery base are made from high impact super tough nylon, offering exceptional durability and weather resistance. All openings are O-ring sealed. Spring loaded clip with built in attachment ring attaches to belts and harnesses. One way valve for case venting. Available in international safety orange or high visibility yellow.

**Dimensions:** Height: 6.75 in. (17.15 cm)      Height in charger: 8 .50 in. (21.6 cm)  
 Width: 2.85 in. (7.24 cm)                      Diameter: 2.87 in. (7.29 cm)

**Grip area:**  
 Height: 3.6 in. (9.14 cm)                      Thickness: 1.35 in. (3.43cm)  
 Width: 2.20 in. (5.59 cm)

**Weight:** 15.4 oz (437 grams)\*

**Lens:** Unbreakable Lexan® Lens with silicone anti-scratch coating is assembled in a heavy duty bezel. O-ring sealed.

**Light Source:** 5.5-watt, black-dot xenon bulb with anti-glare coating has an average life of up to 50 hrs & provides maximum visibility in smoke & fog with less glare, scatter and bounce back.

**Light Output:** Bulb Rating: Up to 25,000 Peak beam candlepower; 114 Lumens typical

**On/Off:** O-ring sealed rotary switch made from flame retardant glass-filled thermoplastic. A ¼" high actuator provides easy operation even when wearing heavy gloves.

**Run Time:** Operational for up to 4.25 continuous hours between charges

**Battery:** Industrial rechargeable nickel-cadmium 4.8 volt, 1.8 amp hour, 4 cell sub-C can be recharged up to 1,000 times. Spare battery pack can be speed-loaded in seconds into the light via a hinged door with stainless steel latch.

**Charging:** AC and DC one-hour fast chargers with full charge indicators designed specifically for AC or DC power sources. The universal Steady Charger, which requires up to 10 hours for a complete charge, can be used with 110V, 120V, 230V, 240V, or 12V DC by exchanging its charge cord.

**Features:**

- Water resistant
- Serialized for positive identification

**Approvals\*\*:** UL Listed for Class I, II, III, Division 2, CUL Listed for Class I, II, III, Division 2, Rack meets requirements of NFPA 1901-12.17 mounted in any position. Most models meet applicable European Community Directives.

**Warranty:** Limited lifetime warranty

\*With battery (included in purchase)



### Survivor® Division 2 Model Part Numbers

#### Steady Charge Model

|                                 |        |        |
|---------------------------------|--------|--------|
| Survivor AC/DC w/Charger/Holder | Yellow | #90243 |
| Survivor AC/DC w/Charger/Holder | Orange | #90043 |
| Survivor – (W/out Charger)      | Yellow | #90244 |
| Survivor – (W/out Charger)      | Orange | #90044 |

#### PiggyBack® Steady Charge Model

|  |        |        |
|--|--------|--------|
| Survivor w/120V AC/12V DCPiggyBack SC  | Yellow | #90265 |
| Survivor w/120V AC/12V DC PiggyBack SC | Orange | #90065 |

#### Fast Charge Model

|                                     |        |        |
|-------------------------------------|--------|--------|
| Survivor w/120 volt AC Fast Charger | Yellow | #90262 |
| Survivor w/120 volt AC Fast Charger | Orange | #90062 |
| Survivor w/12 volt DC Fast Charger  | Yellow | #90264 |
| Survivor w/12 volt DC Fast Charger  | Orange | #90064 |

#### PiggyBack® Fast Charge Model

|                                 |        |        |
|---------------------------------|--------|--------|
| Survivor w/120V AC PiggyBack FC | Yellow | #90241 |
| Survivor w/120V AC PiggyBack FC | Orange | #90041 |
| Survivor w/12V DC PiggyBack FC  | Yellow | #90242 |
| Survivor w/12V DCPiggyBack FC   | Orange | #90042 |

### Survivor® Div 2 Model Accessories Part Numbers

|   |        |
|---|--------|
| Steady Charge (SC) Plug-In Charger Holder | #90010 |
| Steady Charge (SC) PiggyBack Charger      | #90110 |
| AC Fast Charger (Includes Holder)         | #90011 |
| DC #1 Fast Charger (Includes Holder)      | #90012 |
| DC #1 PiggyBackPiggy Fast Charger         | #90013 |
| DC #2 Fast Charger (Includes Holder)      | #90013 |
| DC #2 PiggyBack Fast Charger              | #90113 |
| Bank Charger, (SC) 120 volt AC            | #90400 |
| Bank Charger, DC                          | #90401 |
| 120 volt AC Charge Cord                   | #22311 |
| 12 volt DC1 Charge Cord                   | #22051 |
| 12 volt DC2 Direct Wire Charge Cord       | #22050 |
| Battery Pack Assembly – Division 2        | #90338 |
| Black Dot Xenon Bulb – Division 2         | #90314 |
| Facecap Assembly (Division 1 & 2)*        | #90330 |
| Bezel/Lens Assembly*                      | #90054 |

\*Image not available



|                            |        |        |
|----------------------------|--------|--------|
| Survivor – (W/out Charger) | Yellow | #90244 |
| Survivor – (W/out Charger) | Orange | #90044 |



|                                      |        |
|--------------------------------------|--------|
| 120V AC charge cord                  | #22311 |
| 12V DC cigarette lighter charge cord | #22051 |
| 12V DC direct wire charge cord       | #22050 |



|                                   |        |
|-----------------------------------|--------|
| Black Dot Xenon Bulb – Division 2 | #90314 |
|-----------------------------------|--------|



|                                    |        |
|------------------------------------|--------|
| Battery Pack Assembly – Division 2 | #90338 |
|------------------------------------|--------|



|                                |        |
|--------------------------------|--------|
| Bank Charger, (SC) 120 volt AC | #90400 |
| Bank Charger, DC               | #90401 |



|   |        |
|---|--------|
| AC Fast Charger                                 | #90011 |
| DC #1 Fast Charger (DC Configuration not shown) | #90012 |
| DC #2 Fast Charger (DC Configuration not shown) | #90013 |



|   |        |
|---|--------|
| Steady Charge (SC) Plug-In Charger Holder | #90010 |
| Steady Charge (SC) PiggyBack Charger      | #90110 |